

### Horizontal Single Phase Openwell Submersible Monoblocs (SLICK Series)



Power Range : 0.37 - 1.5 kW  
Flow Rate : 36 - 1.8 m<sup>3</sup>/hr  
Head Range : 8 - 35 metres  
Speed : 2880 rpm

### Sewage Self Priming Monobloc Pumps (SMB Series)



Power Range : 0.7 - 2.2 kW  
Flow Rate : 44.4 - 1.6 m<sup>3</sup>/hr  
Head Range : 6 - 21 metres  
Insulation : Class 'B'  
Speed : 2880 rpm

### Single Phase Centrifugal Monobloc Pumps



Power Range : 0.37 - 1.5 kW  
Flow Rate : 44.4 - 1.02 m<sup>3</sup>/hr  
Head Range : 8 - 34metres  
Insulation : Class 'B'  
Speed : 2880 rpm

### Regenerative Monobloc Pumps (Non-Self Priming Pumps) (MMV Series)



Power Range : 0.37 - 0.75 kW  
Flow Rate : 3.22 - 0.3 m<sup>3</sup>/hr  
Head Range : 6 - 51 metres  
Insulation : Class 'B'  
Speed : 2880 rpm

### Self Priming Regenerative Monobloc Pumps (SMV Series)



Power Range : 0.18 - 0.75 kW  
Flow Rate : 3.2 - 0.3 m<sup>3</sup>/hr  
Head Range : 6 - 51 metres  
Insulation : Class 'B'  
Speed : 2880 rpm

Since 1960  
**MAHENDRA**<sup>®</sup>  
**PUMPS**  
Performance. Value. Trust

**Mahendra Pumps (P) Limited**