

LED Features:

- CREE XLAMP XPG2 LEDS >100 Lm/W
- Available in 11 IES light distributions
- Patented heat dissipation design for optimum efficiency
- Excellent optical presentation for high bays
- Solid State with high-shock and vibration resistance
- Die-cast aluminum housing with custom colors
- Modular design for easy maintenance or upgrade
- Surface mount kit bolts directly to the ceiling or pendant
- High CRI - RA>75 enhances all original colors
- Philips Xitanium Class I 0-10V Dimming Power Supply
- External photocell and motion sensor capable
- No infrared or UV radiation
- Operating Temperature: -40 to 55 degrees celsius
- 100,000 hour LED life - 700mA drive current
- 5 year system warranty
- CE, FCC, RoHS, cUL, UL, CSA - IP66 outdoor rated



Garage / Canopy

Vega SM Series



Models:

- VVDSM014: 14 LEDS - 33W - 3100 Lm - 6.6" (L) - 10.8 lbs
- VVDSM028: 28 LEDS - 62W - 5800 Lm - 9.2" (L) - 12.3 lbs
- VVDSM042: 42 LEDS - 93W - 8800 Lm - 11.8" (L) - 13.8 lbs
- VVDSM056: 56 LEDS - 123W - 12300 Lm - 14.3"(L) - 15.5 Lbs



Ordering: moq = 2 Units

Part #	Color Temp	Lens Type	Voltage	Case Color	Dimming
VVDSM014	W - 2700-3300K	S1M1 - 150 x 90 - Type I Medium	V27 - 100-277V	BK - Black	ND - No Dim
VVDSM028	N - 3700-4300K	S1S1 - 95 x 85 - Type I Short	V48 - 347-480V**	SG - Silver Gray	D1 - 0-10V Dim
VVDSM042	P - 4700-5300K	S1S2 - 95 x 85 - Type I Short Anti-Glare	D12 - 12V DC	WT - White	DL - Dali
VVDSM056	C - 5700-6500K	A2M1 - 150 x 75 - Type II Medium	D24 - 24V DC	BZ - Bronze	PD - Program Dim
	CS - Custom	A2M3 - 145 x 65 - Type II Medium		CS - Custom	(Specify Time Schedule)
	(Specify Kelvin/Nm)	A3L2 - 155 x 100 - Type III Long		(Specify Pantone/RAL)	
		A3M2 - 145 x 45 - Type III Medium			
		S5M1 - 75 Degree - Type V Medium			
		S5N2 - 18 Degree - Type V Narrow			
		S5W2 - 145 Degree - Type V Wide			
		S7M1 - 130 x 30 - Type VII Medium			

Ordering Example:
 VVDSM014-N-S1M1-V27-BK-ND



**CSA & cUL Listed 62W - 308W Only

