

# BL-WA22/WA25

## Superbay Series

The WA22 22" acrylic is designed as the economical solution to all non-impact applications. Clear lighting grade acrylic allows about 20% uplight for a well-lit application.

WA25 acrylic reflector is designed for 15 to 30 foot mounting heights in areas that call for efficient three-dimensional illumination as well as good looks.

Unit Pack available: BL-400P8-WA22-WH-EX-UPL.

All reflectors have field-adjustable reflector brackets for medium to wide lighting distributions. Use coated lamp for best performance. Follow ambient temperature guidelines for long life.

Suitable for damp location.  
Minimum 90°C supply conductors.



ACRYLIC

### ORDERING INFORMATION

<b>BL</b>	-			-		-		-	<b>EX</b>
<b>SERIES</b>			<b>SOURCE</b>		<b>VOLTAGE</b>		<b>COLOR</b>		<b>SOCKET</b>
BL Superbay Series			S High Pressure Sodium P Pulse Start Metal Halide		5 480V 6 Tri-Tap® (120, 277, 347V) 8 Quad Tap® (120, 208, 240, 277V) F 347V		WH White (standard) GR Gray		EX Pink exclusionary socket. Required for PSMH
		<b>WATTAGE</b>					<b>OPTICS</b>		
		175 175w PSMH only 250 250w PSMH or HPS 320 320w PSMH only 400 400w PSMH or HPS					WA22 22" Wide acrylic reflector WA25 25" Wide acrylic reflector		

### ACCESSORIES - Order Separately

Catalog Number	Description
WA2-ENC	Bottom enclosure
WA22-CDL	Conical bottom enclosure
WA22-DLR	Drop lens bottom enclosure
WA25-DLR	Drop lens bottom enclosure

Note: Bottom enclosures are required unless lamps designated as "suitable for open use" are used

Note: Options must be added as suffix to catalog number; Accessories must be ordered separately

Max Ambient Temperature Chart		
Wattage	Open	Enclosed
250 PSMH/HPS	55°C	55°C
320 PSMH	55°C	55°C
400 PSMH	55°C	55°C

For complete temperature information, see page 441.

For a complete list of Options and Accessories see pages 437 to 445.

LEG MOUNT WA22	A	B	C	D	E	F
Quick-On®	24 7/8" - 27 1/8"	22 1/2"	8 5/8"	14"	9 1/2"	1 1/8"
Slick-On®	632 - 689 mm	572 mm	219 mm	356 mm	241 mm	29 mm

FLUSH MOUNT WA22	A	B	C	D	E	F
Quick-On®	22 5/8"	22 1/2"	8 5/8"	14"	9 1/2"	1 1/8"
Slick-On®	575 mm	572 mm	219 mm	356 mm	241 mm	29 mm

LEG MOUNT WA25	A	B	C	D	E	F
Quick-On®	25 7/16" - 27 11/16"	25 3/8"	8 5/8"	14 5/8"	9 1/2"	1 1/8"
Slick-On®	646 - 686 mm	645 mm	219 mm	371 mm	241 mm	29 mm

FLUSH MOUNT WA25	A	B	C	D	E	F
Quick-On®	23 1/4"	25 3/8"	8 5/8"	14 5/8"	9 1/2"	1 1/8"
Slick-On®	591 mm	645 mm	219 mm	371 mm	241 mm	29 mm

