



>LED

Vivid Leds is your **complete source** for Energy Efficient Lighting!

LED Features:

- Philips Lumileds Luxeon Rebel ES LEDs
- Class I Meanwell driver efficiency above 90% - 700mA
- Patented fin design aluminum heatsink structure
- High quality die-cast aluminum processing technique
- Special surface powdercoat treatment process
- Thermal management design with low junction temperature
- Extremely light weight for safety in use and installation
- Easy installation and maintenance with dust prevention
- High resistance in severe outdoor environment - IP65
- National listing lab tested with IES standards
- Provision of diverse lenses ranging from 15 to 135 degrees
- Solid State with high-shock and vibration resistance
- Heavy duty & structually rigid rotating trunnion bracket
- Superior luminous efficiency of 110-130 Lm/W
- Instant on and off without delay or re-strike issues
- High CRI - RA>70 enhances all original colors
- Contains no mercury or lead and cool to the touch
- 0.75mm² triple shield 6.5' cord with optional plug
- Operating temperature: -40 to 45 degrees C
- 100,000 hour LED life
- 5 year system warranty
- Certifications - CE, RoHS, ETL, cETL, DLC

Flood Lights Performance Series



VVDLFL60 - 30 LEDs - 60W - 6,600 Lm - 2.2A
14.4"(H) x 12.9"(W) x 3.6"(D) - 9.9 Lbs



VVDLFL80 - 40 LEDs - 80W - 8,800 Lm - 2.7A
VVDLFL100 - 50 LEDs - 100W - 11,000 Lm - 3.3A
14.4"(H) x 15.2"(W) x 3.6"(D) - 12.2 Lbs

VVDLFL150 - 70 LEDs - 150W - 16,500 Lm - 5.2A
VVDLFL200 - 100 LEDs - 200W - 22,000 Lm - 6.7A
14.4"(H) x 20"(W) x 3.6"(D) - 16.5 Lbs



VVDLFL250 - 120 LEDs - 250W - 27,500 Lm - 8.4A
14.4"(H) x 21.5"(W) x 3.6"(D) - 18.7 Lbs



VVDLFL300 - 140 LEDs - 300W - 33,000 Lm - 10.4A
VVDLFL350 - 162 LEDs - 350W - 38,500 Lm - 12.6A
23.9"(H) x 20"(W) x 4.6"(D) - 32 Lbs



VVDLFL400 - 200 LEDs - 400W - 44,000 Lm - 13.4A
23.9"(H) x 21.5"(W) x 4.6"(D) - 34.2 Lbs

VVDLFL600 - 308 LEDs - 600W - 64,000 Lm - 19.8A
23.9"(H) x 31.9"(W) x 4.6"(D) - 57.3 Lbs

LED POWERED BY:
PHILIPS
LUMILEDS



➔ **Ordering: moq = 2 Units**

Part #	Color Temp	Lens Type	Voltage	Housing	Plug	Accessories
VVDLFL60	23 - 2300-2700K	15 - 15 Degree Round	UNV1 - 90-305V	BK - Black	BW - Bare Wire	DM - 0-10V Dimmable
VVDLFL80	30 - 3000-3500K	30 - 30 Degree Round	UNV2 - 347-480V	WT - White	PG - US Plug	PM - PWM Dimmable
VVDLFL100	40 - 4000-4500K	40 - 40 Degree Round				DA - Dali Dimmable
VVDLFL150	50 - 5000-5500K	60 - 60 Degree Round				90-305VAC
VVDLFL200	60 - 6000-6500K	SYM - 60x135 Symmetrical				
VVDLFL250		ASYM- 85x135 Asymmetrical				
VVDLFL300						
VVDLFL350						
VVDLFL400						
VVDLFL600						

Ordering Example:
VVDLFL60-50-30-UNV1-BK-BW

DLC Qualified Models:
VVDLFL80-30K (3000K), VVDLFL80-57K (5700K),
VVDLFL200-50K (5000K), VVDLFL400-50K (5000K),
VVDLFL600-57K (5700K)

