

### FEATURES

- Highly efficient LEDs provide up to 101 lumens per watt at 70 CRI
- Long-life, 60,000 hour LEDs at L90 reduce life cycle maintenance costs
- 2' size provides nominal lumen packages from 12,950 to 27,750
- 3' size provides nominal lumen packages from 37,850 to 42,100
- Aisle, Medium, or Wide distribution options
- Individual optics for each LED allow for precise control of light distribution
- Operates in a wide range of ambient temperatures
- Extruded aluminum housing acts as heat sink; downward sloping fins minimize debris buildup
- Optional occupancy sensor sits securely within the housing frame
- Fixed output or 0-10V dimming available
- Product designed for quick and easy suspension mounting with aircraft cabling
- CSA listed and suitable for damp locations
- DesignLights Consortium® (DLC) qualified; see [www.designlights.org](http://www.designlights.org)
- Five year warranty (Terms and Conditions apply)



(2' High Lumen Shown)

### ORDERING INFORMATION

| LLHP                     |              |                                  |   |                               |                                    |   |  |  |
|--------------------------|--------------|----------------------------------|---|-------------------------------|------------------------------------|---|--|--|
| MODEL                    | SIZE         | COLOR TEMP                       | LUMEN OUTPUT  | DISTRIBUTION                  | DRIVER                             | VOLTAGE   | OPTIONS  |  |
| LLHP LED Linear High Bay | 2 2'<br>3 3' | 30 3000K<br>40 4000K<br>50 5000K | L Low Lumen (2' size)<br>H High Lumen (2' size)<br>VL Very High Lumen (3' size)<br><small>See Product Availability Table below.</small> | A Aisle<br>M Medium<br>W Wide | E Fixed Output<br>ED 0-10V Dimming | U 120V-277V<br>120 120V<br>277 277V<br>347 347V<br>480 480V | <b>F3C5</b> 3-Conductor Cord 5'<br><b>F3C10</b> 3-Conductor Cord 10'<br><b>F3C15</b> 3-Conductor Cord 15'<br><b>C6TL15_</b> 6' Cord and Twist-Lock Plug 15A (Add Volt 1=120, 2=277)<br><b>CP6TL20_</b> 6' Cord and Twist-Lock Plug 20A (Add Volt 1=120, 2=277)<br><b>WIH</b> wiHUBB Enabled <sup>1</sup><br><b>WG</b> Wire Guard (factory installed)<br><b>OS1</b> Occupancy Sensor 120-277 Single Relay |  |

#### ACCESSORIES (ORDER SEPARATELY)

- CP6TL15\_** 6' Cord and Twist-Lock Plug 15A (Add Volt 1=120, 2=277)
- CP6TL20\_** 6' Cord and Twist-Lock Plug 20A (Add Volt 1=120, 2=277)
- LHVQM5** Aircraft Cable 5' Pair
- LHVQM10** Aircraft Cable 10' Pair
- LHVQM15** Aircraft Cable 15' Pair

<sup>1</sup> In-Fixture Module Antenna adds 2" to overall fixture height at specific location.

### PRODUCT AVAILABILITY

| DISTRIBUTION | SIZE | LUMEN PACKAGE | NOMINAL LUMENS | NOMINAL WATTS | Efficacy |
|--------------|------|---------------|----------------|---------------|----------|
| Aisle        | 2'   | L             | 12,950         | 143           | 91       |
|              | 2'   | H             | 24,850         | 281           | 88       |
|              | 3'   | VL            | 37,850         | 425           | 89       |
| Medium       | 2'   | L             | 14,350         | 142           | 101      |
|              | 2'   | H             | 27,750         | 281           | 99       |
|              | 3'   | VL            | 41,800         | 425           | 98       |
| Wide         | 2'   | L             | 13,900         | 143           | 98       |
|              | 2'   | H             | 27,000         | 281           | 97       |
|              | 3'   | VL            | 42,100         | 425           | 99       |

Lumens vary according to color temperatures and other factors. See specific photometric test(s).

