

LED Features:

- Philips Luxeon T LEDs >110 Lm/W
- Excellent heat dissipation design for optimum efficiency
- National listing lab tested with IES standards
- Multiple light distribution options
- Modular design for easy maintenance or upgrade
- Solid State with high-shock and vibration resistance
- Instant on and off without delay or re-strike
- Angle adjustable trunnion bracket
- Anodized aluminum with anti-static coating
- Mitsubishi polycarbonate shatterproof cover
- Rubber gasket LED ring ensures IP waterproofing
- Smooth finish black or silver powdercoating
- High CRI - RA>80 enhances all original colors
- 0-10V dimmable Meanwell HLG power supply
- Operating Temperature: -40 to 50 degrees celsius
- Power factor: >0.95
- 100,000 hour LED life
- 5 year system warranty
- Certifications: CE, TUV, SAA, RoHS, UL, cUL - IP66

Garage / Canopy

Aero XL Series



Models:

- VVDAK040S: 40W - 4400 Lm - 6" (L) - 7.7 lbs
- VVDAK080S: 80W - 8800 Lm - 9" (L) - 11.4 Lbs
- VVDAK120S: 120W - 13200 Lm - 12.3" (L) - 13.6 Lbs




All Models - 12" (W) x 2.5" (Height without bracket - 7.7" with bracket)

Ordering: MOQ = 2 units

Part #	Color Temp	Beam Angle	Voltage	Housing	Dimming
VVDAK040S	3 - 3000K	15 - Type V 15 Degree	UNV - 100-240V	B - Black	ND - Non-Dimmable
VVDAK080S	4 - 4000K	30 - Type V 30 Degree	277 - 277V	S - Silver	DM - 0-10V Dimmable
VVDAK120S	5 - 5000K	60 - Type V 60 Degree			
	7 - 5700K	90 - Type V 90x100 Degree			
	6 - 6500K	FR - Type V Frosted Cover 120 Degree			
		CL- Type V Clear Cover 120Degree			

LED POWERED BY:
PHILIPS
LUMILEDS



Ordering Example: VVDAK280S-5-60-UNV-B