



H(m)	D(m)	E <sub>max</sub> (lx)
1	0.3	11820
2	0.6	2955
3	0.9	1313
4	1.2	739
5	1.5	473



H(m)	D(m)	E <sub>max</sub> (lx)
1	0.4	8492
2	0.7	2123
3	1.1	944
4	1.4	531
5	1.8	340







H(m)	D(m)	E <sub>max</sub> (lx)
1	0.6	4711
2	1.3	1178
3	1.9	524
4	2.6	294
5	3.2	188


Surface Finish Color ■ Black □ White ■ Silver

IP40


Model No	Luminaire Power (Watt)	Input Current (mA)	Color Temperature (K)	Luminous Flux (lm)	CRI Ra	Luminaire Efficacy (lm/w)	L70 Lifetime (Hours)	SDCM	Beam Angle (°)	Dimming Format	Cut-out (mm)
KT-7120N15-20M15D-830-R-B1-230V-V5	20	500	3000	1460	83	73	50,000	3	15	Triac/1-10V	130
KT-7120N15-20M24D-830-R-B1-230V-V5	20	500	3000	1460	83	73	50,000	3	24	Triac/1-10V	130
KT-7120N15-20M38D-830-R-B1-230V-V5	20	500	3000	1460	83	73	50,000	3	38	Triac/1-10V	130
KT-7120N15-20M60D-830-R-B1-230V-V5	20	500	3000	1460	83	73	50,000	3	60	Triac/1-10V	130
KT-7120N16-20M15D-840-R-B1-230V-V5	20	500	4000	1585	83	79	50,000	3	15	Triac/1-10V	130
KT-7120N16-20M24D-840-R-B1-230V-V5	20	500	4000	1585	83	79	50,000	3	24	Triac/1-10V	130
KT-7120N16-20M38D-840-R-B1-230V-V5	20	500	4000	1585	83	79	50,000	3	38	Triac/1-10V	130
KT-7120N16-20M60D-840-R-B1-230V-V5	20	500	4000	1585	83	79	50,000	3	60	Triac/1-10V	130



H(m)	D(m)	E <sub>max</sub> (lx)
1	0.3	11820
2	0.6	2955
3	0.9	1313
4	1.2	739
5	1.5	473



H(m)	D(m)	E <sub>max</sub> (lx)
1	0.4	8492
2	0.7	2123
3	1.1	944
4	1.4	531
5	1.8	340



H(m)	D(m)	E <sub>max</sub> (lx)
1	0.6	4711
2	1.3	1178
3	1.9	524
4	2.6	294
5	3.2	188

Surface Finish Color ■ Black □ White ■ Silver

IP40

Model No	Luminaire Power (Watt)	Input Current (mA)	Color Temperature (K)	Luminous Flux (lm)	CRI Ra	Luminaire Efficacy (lm/w)	L70 Lifetime (Hours)	SDCM	Beam Angle (°)	Dimming Format	Cut-out (mm)
KT-7120N16-20M15D-830-R-B2-230V-V5	20	500	3000	1620	83	81	50,000	3	15	Triac/1-10V	130
KT-7120N16-20M24D-830-R-B2-230V-V5	20	500	3000	1620	83	81	50,000	3	24	Triac/1-10V	130
KT-7120N16-20M38D-830-R-B2-230V-V5	20	500	3000	1620	83	81	50,000	3	38	Triac/1-10V	130
KT-7120N16-20M60D-830-R-B2-230V-V5	20	500	3000	1620	83	81	50,000	3	60	Triac/1-10V	130
KT-7120N18-20M15D-840-R-B2-230V-V5	20	500	4000	1760	83	88	50,000	3	15	Triac/1-10V	130
KT-7120N18-20M24D-840-R-B2-230V-V5	20	500	4000	1760	83	88	50,000	3	24	Triac/1-10V	130
KT-7120N18-20M38D-840-R-B2-230V-V5	20	500	4000	1760	83	88	50,000	3	38	Triac/1-10V	130
KT-7120N18-20M60D-840-R-B2-230V-V5	20	500	4000	1760	83	88	50,000	3	60	Triac/1-10V	130