




Box specification	IJK or SAK terminals specification and quantity						Ways of outlet	G15	G20	G25	G32	G40	G50	G70	G80	G100
	2.5 <sup>2</sup>	4 <sup>2</sup>	6 <sup>2</sup>	10 <sup>2</sup>	16 <sup>2</sup>	35 <sup>2</sup>										
	22	20	18	15	12	—	D/X	8	6	4	3	2	2	—	—	—
							L/R	8	6	4	3	2	2	—	—	—
	22	20	18	15	12	—	D/X	10	8	5	4	3	2	2	—	—
							L/R	8	6	4	3	2	2	—	—	—
	31	29	23	18	15	12	D/X	10	8	5	4	3	2	2	—	—
							L/R	10	8	5	4	3	2	2	—	—
	44	42	23	18	—	—	D/X	10	8	5	4	3	2	2	—	—
							L/R	10	8	5	4	3	2	2	—	—
	40	38	30	24	20	16	D/X	12	10	7	5	4	3	2	—	—
							L/R	12	10	7	5	4	3	2	—	—
	68	66	48	40	—	—	D/X	12	10	7	5	4	3	2	—	—
							L/R	12	10	7	5	4	3	2	—	—
	40	38	30	24	20	16	D/X	18	12	10	8	8	4	4	3	2
							L/R	18	12	10	8	8	4	4	3	2
	68	66	48	40	—	—	D/X	18	12	10	8	8	4	4	3	2
							L/R	18	12	10	8	8	4	4	3	2

Note: The specifications and size are only for reference, they can be designed and manufactured on request.

### ■ Outline & installation dimensions



Box specification C × D (mm)	A (mm)	B (mm)	E (mm)
220 × 220	170	270	150
220 × 260	170	310	150
260 × 260	210	310	150
330 × 330	280	380	150
350 × 350	300	400	200